



An opal circular luminaire with a contemporary design.

PLEXI ROUND UP/ DOWN is a piece of architecture, perfect for adding stature to an area.

With its gentle uniform lighting, it upgrades areas such as lobbies, corridors, offices, stores and homes.

It is available with five diameters: 300, 350, 450, 620 and 900mm.

Technical Features

- Aluminium body, painted electrostatically in selected colour.
- Version with opal plexi glass or microprismatic cover.
- Direct and indirect illumination.
- Pure light without IR/UV radiation.
- Efficient thermal management.
- Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10).
- Connection for operation on 230V-50/60Hz.


Upon Request

- Connection for emergency lighting system, for one or three hours.
- At bigger dimensions.

PLEXI ROUND UP/ DOWN


ARCHITECTURAL SURFACE & PENDANT LUMINAIRES

PLEXI ROUND UP / DOWN




- High efficient opal plexiglass cover.
- CRI: min. 80 / SDCM: 3

PLEXI ROUND UP/ DOWN 450




PLEXI ROUND UP/ DOWN 620



Code	Description		Dimensions mm	
			ØA	B
8232098	Plexi Round 300 Up/Down LED 20W Warm	Luminous Efficacy: 90 Lm/Watt	300	140
8232108	Plexi Round 300 Up/Down LED 20W Neutral	Luminous Efficacy: 95 Lm/Watt	300	140
8232138	Plexi Round 350 Up/Down LED 20W Warm	Luminous Efficacy: 90 Lm/Watt	350	140
8232148	Plexi Round 350 Up/Down LED 20W Neutral	Luminous Efficacy: 95 Lm/Watt	350	140
8232078	Plexi Round 450 Up/Down LED 24W Warm	Luminous Efficacy: 206 Lm/Watt at 250mA	450	140
8232088	Plexi Round 450 Up/Down LED 24W Neutral	Luminous Efficacy: 195 Lm/Watt at 250mA	450	140
8232118	Plexi Round 620 Up/Down LED 60W Warm	Luminous Efficacy: 206 Lm/Watt at 250mA	620	140
8232128	Plexi Round 620 Up/Down LED 60W Neutral	Luminous Efficacy: 195 Lm/Watt at 250mA	620	140
8232158	Plexi Round 900 Up/Down LED 110W Warm	Luminous Efficacy: 206 Lm/Watt at 250mA	900	160
8232168	Plexi Round 900 Up/Down LED 110W Neutral	Luminous Efficacy: 195 Lm/Watt at 250mA	900	160

For dimmer version add letter “D” at the end of product code.

PLEXI ROUND UP / DOWN MICROPRISMATIC




- High efficient microprismatic cover.
- CRI: min. 80 / SDCM: 3

Code	Description		Dimensions mm	
			ØA	B
8236098	Plexi Round 300 Up/Down Microprismatic LED 20W Warm	Luminous Efficacy: 90 Lm/Watt	300	140
8236108	Plexi Round 300 Up/Down Microprismatic LED 20W Neutral	Luminous Efficacy: 95 Lm/Watt	300	140
8236138	Plexi Round 350 Up/Down Microprismatic LED 20W Warm	Luminous Efficacy: 90 Lm/Watt	350	140
8236148	Plexi Round 350 Up/Down Microprismatic LED 20W Neutral	Luminous Efficacy: 95 Lm/Watt	350	140
8236078	Plexi Round 450 Up/Down Microprismatic LED 24W Warm	Luminous Efficacy: 206 Lm/Watt at 250mA	450	140
8236088	Plexi Round 450 Up/Down Microprismatic LED 24W Neutral	Luminous Efficacy: 195 Lm/Watt at 250mA	450	140
8236118	Plexi Round 620 Up/Down Microprismatic LED 60W Warm	Luminous Efficacy: 206 Lm/Watt at 250mA	620	140
8236128	Plexi Round 620 Up/Down Microprismatic LED 60W Neutral	Luminous Efficacy: 195 Lm/Watt at 250mA	620	140
8236158	Plexi Round 900 Up/Down Microprismatic LED 110W Warm	Luminous Efficacy: 206 Lm/Watt at 250mA	900	160
8236168	Plexi Round 900 Up/Down Microprismatic LED 110W Neutral	Luminous Efficacy: 195 Lm/Watt at 250mA	900	160

For dimmer version add letter “D” at the end of product code.

ADJUSTABLE SUSPENSION



- Stainless steel cable and regulators.
- With aluminium rosette Ø125.
- With transparent cable 3x0,75mm² or 5x0,50mm² for dimmer.

Code	Description	L	Kg
80231	Suspension - Power Supply 3x0,75mm²	2000	0,300
80232	Suspension - Power Supply 3x0,75mm²	3000	0,300
80233	Suspension - Power Supply 5x0,50mm²	2000	0,300
80234	Suspension - Power Supply 5x0,50mm²	3000	0,300

Colour Codes:

0 Colours 1 White 2 Titan 3 Black

PLEXI ROUND UP/ DOWN

ARCHITECTURAL SURFACE & PENDANT LUMINAIRES



