

The MLM surface-mounted luminaire provides perfect lighting comfort and uniform, glare-free lighting.

The luminaire unit impresses with its low profile, while slim-line design is emphasised by its linear contours.

Technical Features

- Steel body with flat form, electrostatically painted in white colour.
- High efficient parabolic louvre from specular aluminium.
- Aluminium louvre with high efficient satin PMMA cover for louvre version.
- Last generation high efficient LED CHIP.
- Pure light without IR/UV radiation.
- UGR < 19 at specific editions:

Glare Evaluation: X=4H/Y=8H S=0,25H, reflection factors 70/50/20.

For DSE work stations: $\gamma \ge 65^{\circ} < 3000 \text{cd/m}^2$.

- Connection for operation on 230V-50/60Hz.

High Efficiency

- Operation life: 50,000 hours with efficiency > 90% of the initial luminous flux (L90B10).

High Output

- Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10).

Upon request:

- Body and accessories in various colours (RAL)
- Connection for emergency lighting system, for one or three hours.


/ 186 / www.petridis-lighting.gr

MLM


MLM LED

PROFESSIONAL SURFACE & PENDANT LUMINAIRES











- Steel body.
- Aluminium louvre with high efficient satin PMMA cover for led source.
- Suspension and power supply not included. CRI: min. 80 / SDCM: 3
- Luminous Efficacy: High Efficiency 211 Lm/Watt 4000K 199 Lm/Watt 3000K


High Output -203 Lm/Watt 4000K

192 Lm/Watt 3000K

Code	Description (High Efficiency 200mA)	W x L (mm)
29158	MLM LED 28W 3 rows Warm	597x597
29159	MLM LED 28W 3 rows Neutral	597x597
29162	MLM LED 38W 4 rows Warm	597x597
29163■	MLM LED 38W 4 rows Neutral	597x597
29142	MLM LED 20W Warm	297x597
29143	MLM LED 20W Neutral	297x597
29146■	MLM LED 29W Warm	297x897
29147■	MLM LED 29W Neutral	297x897
29150≡	MLM LED 38W Warm	297x1197
29151■	MLM LED 38W Neutral	297x1197
29154■	MLM LED 48W Warm	297x1497
29155■	MLM LED 48W Neutral	297x1497

Code	Description (High Output 300mA)	W x L (mm)
29160≡	MLM LED 43W 3 rows Warm	597x597
29161■	MLM LED 43W 3 rows Neutral	597x597
29164Ⅲ	MLM LED 58W 4 rows Warm	597x597
29165■	MLM LED 58W 4 rows Neutral	597x597
29144Ⅲ	MLM LED 30W Warm	297x597
29145≣	MLM LED 30W Neutral	297x597
29148	MLM LED 44W Warm	297x897
29149■	MLM LED 44W Neutral	297x897
29152■	MLM LED 58W Warm	297x1197
29153	MLM LED 58W Neutral	297x1197
29156■	MLM LED 72W Warm	297x1497
29157■	MLM LED 72W Neutral	297x1497

For dimmer version add letter " $\ensuremath{\textbf{D}}$ " at the end of product code.



Colour Codes: 0 Colours 1 White 2 Titan

www.petridis-lighting.gr / 187 /