



Technical Features


- Polycarbonate body in white colour.
- Methacrylate cover in white colour.
- Metal steel base for the installation of the led module and the electrical connection.
- Anti-aging sealing gasket.
- Connection for operation on 230V-50/60Hz.

For LED Version:

- Last generation high efficient LED CHIP.
- Pure light without IR/UV radiation.
- Operation life: 50,000 hours with efficiency > 70% of the initial luminous flux (L70B50).

CIRCLIGHT CL/SQUARELIGHT SQL


CIRCLIGHT CL LED



- CRI: min. 80
- Dimmer phase cut (for CL 260)
- Luminous Efficacy:
 - 12W: 126 LM/W at 4000K / SDCM: 3
 - 12W: 120 LM/W at 3000K / SDCM: 3
 - 22W: 116 LM/W at 4000K / SDCM: 4
 - 22W: 105 LM/W at 3000K / SDCM: 4

Code	Description	Dimensions	
		D(mm)	H(mm)
562833	CL 260 LED 12W IP54 Warm	Ø260	55
562843	CL 260 LED 12W IP54 Neutral	Ø260	55
562813	CL 360 LED 22W IP65 Warm	Ø360	83
562823	CL 360 LED 22W IP65 Neutral	Ø360	83

SQUARELIGHT SQL LED



- CRI: min. 80
- Dimmer phase cut (for SQL 200)
- Luminous Efficacy:
 - 12W: 126 LM/W at 4000K / SDCM: 3
 - 12W: 120 LM/W at 3000K / SDCM: 3
 - 22W: 116 LM/W at 4000K / SDCM: 4
 - 22W: 105 LM/W at 3000K / SDCM: 4

Code	Description	Dimensions		
		A(mm)	B(mm)	H(mm)
572843	SQL 200 LED 12W IP54 Warm	200	200	58
572853	SQL 200 LED 12W IP54 Neutral	200	200	58
572823	SQL 300 LED 22W IP65 Warm	300	300	83
572833	SQL 300 LED 22W IP65 Neutral	300	300	83

CL 360 / SQL 300

