



*An opal circular luminaire with a contemporary design.
PLEXI ROUND is a piece of architecture, perfect for adding stature
to an area.
With it's gentle uniform lighting, it upgrades areas such as lobbies,
corridors, offices, stores and homes.
It is available in five diameters: 300, 350, 450, 620 and 900mm.*

Technical Features

- Aluminium body, painted electrostatically in selected colour.
- Version with opal plexi glass or microprismatic cover.
- Direct illumination.
- Pure light without IR/UV radiation.
- Efficient thermal management.
- Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10).
- Connection for operation on 230V-50/60Hz.

Upon Request

- Connection for emergency lighting system, for one or three hours.
- At bigger dimensions.


PLEXI ROUND

ARCHITECTURAL SURFACE & PENDANT LUMINAIRES




PLEXI ROUND

PLEXI ROUND




- High efficient opal plexiglass cover.
- CRI: min. 80 / SDCM: 3

PLEXI ROUND 300 / 350




PLEXI ROUND 450 / 620 / 900



Code	Description		Dimensions mm	
			ØA	B
8231098	Plexi Round 300 LED 20W Warm	Luminous Efficacy: 90 Lm/Watt	300	140
8231108	Plexi Round 300 LED 20W Neutral	Luminous Efficacy: 95 Lm/Watt	300	140
8231138	Plexi Round 350 LED 20W Warm	Luminous Efficacy: 90 Lm/Watt	350	140
8231148	Plexi Round 350 LED 20W Neutral	Luminous Efficacy: 95 Lm/Watt	350	140
8231078	Plexi Round 450 LED 24W Warm	Luminous Efficacy: 206 Lm/Watt at 250mA	450	140
8231088	Plexi Round 450 LED 24W Neutral	Luminous Efficacy: 195 Lm/Watt at 250mA	450	140
8231118	Plexi Round 620 LED 60W Warm	Luminous Efficacy: 206 Lm/Watt at 250mA	620	140
8231128	Plexi Round 620 LED 60W Neutral	Luminous Efficacy: 195 Lm/Watt at 250mA	620	140
8231158	Plexi Round 900 LED 110W Warm	Luminous Efficacy: 206 Lm/Watt at 250mA	900	160
8231168	Plexi Round 900 LED 110W Neutral	Luminous Efficacy: 195 Lm/Watt at 250mA	900	160

For dimmer version add letter “D” at the end of product code.

PLEXI ROUND MICROPRISMATIC




- High efficient microprismatic cover.
- CRI: min. 80 / SDCM: 3

Code	Description		Dimensions mm	
			ØA	B
8235098	Plexi Round 300 Microprismatic LED 20W Warm	Luminous Efficacy: 90 Lm/Watt	300	140
8235108	Plexi Round 300 Microprismatic LED 20W Neutral	Luminous Efficacy: 95 Lm/Watt	300	140
8235138	Plexi Round 350 Microprismatic LED 20W Warm	Luminous Efficacy: 90 Lm/Watt	350	140
8235148	Plexi Round 350 Microprismatic LED 20W Neutral	Luminous Efficacy: 95 Lm/Watt	350	140
8235078	Plexi Round 450 Microprismatic LED 24W Warm	Luminous Efficacy: 206 Lm/Watt at 250mA	450	140
8235088	Plexi Round 450 Microprismatic LED 24W Neutral	Luminous Efficacy: 195 Lm/Watt at 250mA	450	140
8235118	Plexi Round 620 Microprismatic LED 60W Warm	Luminous Efficacy: 206 Lm/Watt at 250mA	620	140
8235128	Plexi Round 620 Microprismatic LED 60W Neutral	Luminous Efficacy: 195 Lm/Watt at 250mA	620	140
8235158	Plexi Round 900 Microprismatic LED 110W Warm	Luminous Efficacy: 206 Lm/Watt at 250mA	900	160
8235168	Plexi Round 900 Microprismatic LED 110W Neutral	Luminous Efficacy: 195 Lm/Watt at 250mA	900	160

For dimmer version add letter “D” at the end of product code.

PLEXI ROUND

ADJUSTABLE SUSPENSION



Colour Codes:

0 Colours 1 White 2 Titan 3 Black

ARCHITECTURAL SURFACE & PENDANT LUMINAIRES



- Stainless steel cable and regulators.
- With aluminium rosette Ø125.
- With transparent cable 3x0,75mm² or 5x0,50mm² for dimmer.

Code	Description	L	Kg
80231	Suspension - Power Supply 3x0,75mm²	2000	0,300
80232	Suspension - Power Supply 3x0,75mm²	3000	0,300
80233	Suspension - Power Supply 5x0,50mm²	2000	0,300
80234	Suspension - Power Supply 5x0,50mm²	3000	0,300

