


DAFNI is surface wall mounted luminaire with LED source, ideal for a wide range of indoor applications.

Technical Features

- Aluminium body, painted electrostatically in selected colour.
- Aluminium mounting base.
- Connection for operation with 230V/50Hz.





/ 494 / www.petridis-lighting.gr

DAFNI

WALL LIGHTING INTERIOR

DAFNI 1









- Aluminium body.
- Aluminium mounting base.
- 230V/50Hz.
- CRI: min. 80 / SDCM: 3
- 2W+2W Up/ Down.
- Luminous Efficacy: 140 Lm/W at 4000 K 132 Lm/W at 3000 K

Code	Description	Kg
88472■	DAFNI 1 2W+2W Warm	0,380
88473■	DAFNI 1 2W+2W Neutral	0,380

DAFNI 2










- Aluminium body.
- Aluminium mounting base.
- 230V/50Hz.
- CRI: min. 80 / SDCM: 3
- 2W+2W Up/ Down.
- Luminous Efficacy: 140 Lm/W at 4000 K 132 Lm/W at 3000 K

Code	Description	Kg
88474■	DAFNI 2 2W+2W Warm	0,320
88475	DΔFML2 2W ± 2W Neutral	0.320

DAFNI 3







- Aluminium body.
- Aluminium mounting base.
- 230V/50Hz.
- CRI: min. 80 / SDCM: 3
- 2W+2W Up/ Down.
- Luminous Efficacy:
 140 Lm/W at 4000 K
 132 Lm/W at 3000 K

Code	Description	Kg
88476	DAFNI 3 2W+2W Warm	0,350
88477■	DAFNI 3 2W+2W Neutral	0,350

 Colour Codes:

 0
 Colours
 1
 White
 2
 Titan
 3
 Black

www.petridis-lighting.gr / 495 /