LITO WALL LIGHTING INTERIOR



LITO is an minimal applique with LED CHIP. It is ideal for hotels, reception halls, bars, restaurants, houses etc.

Technical Features

- Body from aluminium painted electrostatically in selected colour or plated.
- Steel mounting base.
- Pure light without IR/UV radiation.
- Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10).
- Connection for operation with 230V/50Hz.


Upon request:

Available with highest colour rendering index (CRI)

/ 476 / www.petridis-lighting.gr

WALL LIGHTING INTERIOR LITO

LIT0






- Aluminium body.Opal PMMA diffuser.
- 230V/50Hz.
- CRI: min. 80 / SDCM: 3 Luminous Efficacy: 116 Lm/W at 4000 K 110 Lm/W at 3000 K

Code	Description	Kg
85926■	LITO LED 8W Warm	0,550
85927■	LITO LED 8W Neutral	0,550

LITO BIG







- Aluminium body.Opal PMMA diffuser.
- 230V/50Hz.
- CRI: min. 80 / SDCM: 3 Luminous Efficacy: 116 Lm/W at 4000 K 110 Lm/W at 3000 K

Code	Description	Kg
85928■	LITO BIG LED 8W Warm	0,720
85929■	LITO BIG LED 8W Neutral	0,720



www.petridis-lighting.gr / 477 /