



A recessed luminaire with LED technology and high protection degree (IP65). It is ideal for outdoor lighting and for impressive highlighting of facades.


Technical Features

- Aluminium body, painted electrostatically in white colour.
- Tempered protection glass 3mm.
- Pure light without IR/UV radiation.
- Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10).
- Supplied with 2x0,75mm NEOPRENE 1m cable.


Upon Request

- Available at 2700K.
- Available with highest colour rendering index (CRI).


VIVO 1 IP65 SPOT




VIVO 1 IP65 MEDIUM




VIVO 1 IP65 WIDE




VIVO 2 IP65 SPOT



VIVO 2 IP65 MEDIUM



VIVO 2 IP65 WIDE



VIVO IP65

OUTDOOR



VIVO 1 IP65



- Aluminium body.
- Lens in Spot, Medium and Wide.
- 4W power consumption driven at 350mA.
- CRI: min. 80 / SDCM: 3.
- Luminous Efficacy:
4W: 4000 K: 112 Lm/Watt
4W: 3000 K: 100 Lm/Watt

Code	Description	Kg
88164	VIVO 1 4W IP65	0,130

36mm



DRIVERS DIMMER

	DRIVER	DRIVERS DIMMER	
		350mA 18W IP20	350mA 18W IP20
	350mA 18W IP67	103x67x21	146,5x44x30
	140x30x22	1-10/ Push B.	Dali/ Push B.
CODES	MODULES	800036*	800040*
88164	VIVO 1 4W IP65	1 - 3 modules	1 - 4 modules

* Installation in a separate wicket



VIVO 2 IP65



- Aluminium body.
- Reflector in Spot, Medium and Wide.
- 6W power consumption driven at 350mA.
- CRI: min. 80 / SDCM: 3.
- Luminous Efficacy:
6W: 4000 K: 150 Lm/Watt
6W: 3000 K: 144 Lm/Watt

Code	Description	Kg
88147	VIVO 2 6W IP65	0,180

50mm



DRIVERS DIMMER

	DRIVER	DRIVERS DIMMER	
		350mA 18W IP20	350mA 18W IP20
	350mA 18W IP67	103x67x21	146,5x44x30
	140x30x22	1-10/ Push B.	Dali/ Push B.
CODES	MODULES	800036*	800040*
88147	VIVO 2 6W IP65	1 - 2 modules	1 - 3 modules

* Installation in a separate wicket

LED COLOUR CODES:	BEAM CODES:	Colour Codes:
2 Warm 3 Neutral	01 spot 02 medium 03 wide	0 Colours 1 White 2 Titan 3 Black