



This Applique combines the architectural style with the efficiency. It produces perfect lighting conditions without annoying reflections and that is why it can be used from entrance areas to offices. It escapes the restrictions of the T16 lamp by using LED lighting points that can have any spacing pitch and this gives the light line enormous flexibility.

The visual benefit: The continuous-row system is illuminated absolutely uniformly from beginning to end, is economically efficient, is maintenance-free and it has long service life.

Technical Features

- Housing from aluminium profile, painted electrostatically in selected colour.
- PMMA cover.
- Pure light without IR/UV radiation.
- Efficient thermal management.
- Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10).
- Connection for operation on 230V-50/60Hz.

Upon request:

- Available with highest colour rendering index (CRI).
- At special dimensions.



- Aluminium body, painted electrostatically in selected colour.
- PMMA cover.
- Driver 24V DC included.
- CRI: min. 80 / SDCM: 3
- Luminous Efficacy:
140Lm/W at 4000 K
133Lm/W at 3000 K

Code	Description	L	Kg
8200707	Morfi Applique Up/ Down 15W+15W	1000	1,200
8200708	Morfi Applique Up/ Down 23W+23W	1500	2,000

For dimmer version add letter “D” at the end of product code.

Led Colour:	Colour Codes:
<div>2 Warm</div> <div>3 Neutral</div>	<div>0 Colours</div> <div>1 White</div> <div>2 Titan</div> <div>3 Black</div>

