Recessed Spotlights & Downlights

THRIVE



THRIVE is a highly innovative recessed spot, without rotation. It is ideal for smooth ambient lighting or accent lighting inside display cabinets.

The last generation LED chip ensures excellent performance with maximum energy efficiency.

This, in combination with an efficient thermal management, makes Thrive a warranty for premium lighting with LED technology.

Technical Features

- Aluminium body, painted electrostatically in selected colour.
- Easy mounting with clips.
- Pure light without IR/UV radiation.
- Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10).
- Supplied with 2x0,75mm 0,5m cable.


Upon request:

Available with highest colour rendering index (CRI)

/ 220 / www.petridis-lighting.gr

THRIVE

THRIVE



Recessed Spotlights & Downlights




- Beams: Medium, Wide.
- 6W power consumption driven at 700mA.
- CRI: min. 80 / SDCM: 3.
- Luminous Efficacy:

6W: 4000 K: 159 Lm/Watt 6W: 3000 K: 155 Lm/Watt

Code	Description	Kg
88148	THRIVE 6W	0,160

THRIVE AS





C€	F	IP 44	LED	years 5 WARRANTY	ta 25°C	not Included
(o o	000			<u>↑</u> 8-15mm		

- Asymmetrical beam.
- 6W power consumption driven at 700mA.
- CRI: min. 80 / SDCM: 3.
- Luminous Efficacy:

6W: 4000 K: 159 Lm/Watt 6W: 3000 K: 155 Lm/Watt

Code	Description	Kg
88149■■	THRIVE AS 6W	0,160

DRIVERS DIMMER

	I	DRIVERS		700mA 38W	700mA 50W
	700mA 6,5	3W 700mA 30W	103x67x21	146,5x44x30	124x79x22
	58x28,5x2	21 146,5x43,7x30	1-10/Push B.	Dali/Push B.	1-10/Push B./Dali
CODES MODU	LES 800015	800032	800040*	800038*	800042**
88148	6W 1 modul AS 6W 1 modul		1 - 5 modules 1 - 5 modules	1 - 5 modules 1 - 5 modules	1 - 8 modules 1 - 8 modules

Please order modules and drivers separately

- * Installation in a separate wicket
- ** Installation in a separate wicket / Please order **synchronization cable** for each dimmer driver separately Code: 800044 (4m)



www.petridis-lighting.gr / 221 /