

Technical Features

- Body and cover in die-cast aluminum with minimum EN 47100 title with low content copper and high resistance to atmospheric agents.
- Pressure compensation filter in Teflon.
- Gaskets in anti-aging rubber, removable.
- Extra-clear tempered glass, 5 mm thick, with aesthetic silkscreen print in silver.
- Closure screws in stainless steel with TORX T20 imprint.
- External screws in stainless steel.
- Opening provides access to optics and cable box in a single and easy step by using two solid stainless screws.
- Galvanized steel bracket painted in Silver color.
- For the adjustment of floodlight, the floodlight with aluminum lateral protractor scale.
- Power supply cable through a cable gland PG13.
- Power correction factor at full load > 0.9.
- Power supply 220 240V / 50 60 Hz VAC.
- PLUS optic: symmetric optic designed in-house in two different beams, in order to meet different illumination needs.
- The optic consists of high purity aluminum (99,99%) reflectors, with elevated reflectance and performance.
- Available optics:
- MB optic Medium beam: 2x26°; with specular finishing;(*)
- WB optic Wide beam: 2x40°; with peened finishing.
- Available at Symmetric and Asymmetric editions.

Protection Against Surges

- CL I: up to 10kV in common mode and 6kV in differential mode.

Upon Request

- At colour temperature 3000K.





HO7RN-F To ensure the degree of protection (sealing), the use of flexible power supply cable type HO7RN-F (in appropriate diameter) is required.


/ 798 / www.petridis-lighting.gr


NEXT 8

LUMINAIRES WITH EXTRA PROTECTION











- Beams: Medium, Wide.
- Aluminium body.
- Colour temperature 4000K.
- CRI: min. 70.

Code	Description	Lumen Output	Kg
		(from luminaire)	
718813 2	Next 8 Sym. Led 312W 4000K Titan	47400	14,200
718823 2	Next 8 Sym. Led 400W 4000K Titan	58000	14,200
			_
718833002	Next 8 Asym. Led 270W 4000K Titan	39600	14,200
718843002	Next 8 Asym. Led 334W 4000K Titan	47200	14,200







www.petridis-lighting.gr / 299 /