

AGIS LED

OUTDOOR

*A tubular luminaire with simple design and a wide light distribution.  
The IP67 protection allows even external use.  
Applicable to light buildings, residential and industrial areas,  
and adaptable to various architectural geometries and creative  
lighting applications.*

#### **Technical Features**

- Opal tube in PMMA, in four different lengths.
- Integrated control gear.
- Aluminium end caps with inox cable gland.
- Through wiring 3x0,75mm<sup>2</sup> (or 5x0,75mm<sup>2</sup> for dimmer version), external 1m.
- Pure light without IR/UV radiation.
- 120° light beam distribution.
- Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10).
- Connection for operation with 230V/50Hz.



# AGIS LED

OUTDOOR

## AGIS LED



13,5W 660mm, 19,5W 940mm,  
25W 1220mm, 31W 1500mm




- PMMA body.
- Aluminium end caps.
- Luminous Efficacy:  
206 Lm/Watt at 4000K 250mA  
195 Lm/Watt at 3000K 250mA

Code	Description	LM	Kg
850700	Agis LED 13,5W 0,66m Warm	1990	1,500
850710	Agis LED 13,5W 0,66m Neutral	2170	1,500
850740	Agis LED 19,5W 0,94m Warm	2990	1,850
850750	Agis LED 19,5W 0,94m Neutral	3260	1,850
850780	Agis LED 25W 1,22m Warm	3980	2,200
850790	Agis LED 25W 1,22m Neutral	4340	2,200
850820	Agis LED 31W 1,50m Warm	4980	2,600
850830	Agis LED 31W 1,50m Neutral	5430	2,600
850701	Agis LED 13,5W 0,66m Warm Continuous*	1990	1,500
850711	Agis LED 13,5W 0,66m Neutral Continuous*	2170	1,500
850741	Agis LED 19,5W 0,94m Warm Continuous*	2990	1,850
850751	Agis LED 19,5W 0,94m Neutral Continuous*	3260	1,850
850781	Agis LED 25W 1,22m Warm Continuous*	3980	2,200
850791	Agis LED 25W 1,22m Neutral Continuous*	4340	2,200
850821	Agis LED 31W 1,50m Warm Continuous*	4980	2,600
850831	Agis LED 31W 1,50m Neutral Continuous*	5430	2,600

\* For dimmer version add letter "D" at the end of product code.

\* For making continuous row with AGIS it's necessary to use the simple version as the end part.



## AGIS - ACCESSORIES



Code	Description	Kg
805112	Set for surface mounted installation (set 2 pieces)	0,050
805113	Set for pendant installation 1m. (set 2 pieces)	0,050
801105	Connector 4-pole IP68	0,050