


CYCLONE

ARCHITECTURAL SURFACE & PENDANT LUMINAIRES



This luminaire combines the architectural style with the efficiency. It produces perfect lighting conditions without annoying reflections and that is why it can be used from entrance areas to offices. It escapes the restrictions of the T16 lamp by using LED lighting points that can have any spacing pitch and this gives the light line enormous flexibility.




The visual benefit: The continuous-row system is illuminated absolutely uniformly from beginning to end, is economically efficient, is maintenance-free and it has long service life.

Technical Features

- Aluminium body, painted electrostatically in selected colour.
- High efficient satin cover.
- Direct illumination.
- Pure light without IR/UV radiation.
- Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10).
- Connection for operation on 230V-50/60Hz.



Upon request:

- Connection for emergency lighting system, for one or three hours.
- With microprismatic cover (only for Cyclone Slim version) *.
- With Moss **.
- With Acoustic Panel ***.



CYCLONE

CYCLONE



CE

F

CB

IP 20

LED

5 YEARS WARRANTY

ta
25°C



Included

- Aluminium body, painted electrostatically in selected colour.
- High efficient satin cover.
- CRI: min. 80 / SDCM: 3
- Luminous Efficacy:
203 Lm/W at 4000K 300mA
192 Lm/W at 3000K 300mA
- Upon request in Up Down edition.

Code	Description	Dimensions mm		
		ØA	ØB	C
8241012	Cyclone 1 43W Warm	700	420	120
8241013	Cyclone 1 43W Neutral	700	420	120
8241022	Cyclone 2 56W Warm	900	620	120
8241023	Cyclone 2 56W Neutral	900	620	120
8241032	Cyclone 3 79W Warm	1200	920	120
8241033	Cyclone 3 79W Neutral	1200	920	120
8241042	Cyclone 4 92W Warm	1400	1120	120
8241043	Cyclone 4 92W Neutral	1400	1120	120

For dimmer version add letter “D” at the end of product code.

CYCLONE SLIM



CE

F

CB

IP 20

LED

5 YEARS WARRANTY

ta
25°C

Included

- Aluminium body, painted electrostatically in selected colour.
- High efficient satin cover.
- CRI: min. 80 / SDCM: 3
- Luminous Efficacy:
203 Lm/W at 4000K 300mA
192 Lm/W at 3000K 300mA

Code	Description	Dimensions mm		
		ØA	ØB	C
8241052	Cyclone Slim 1 38W Warm *	600	450	80
8241053	Cyclone Slim 1 38W Neutral *	600	450	80
8241062	Cyclone Slim 2 52W Warm	800	650	80
8241063	Cyclone Slim 2 52W Neutral	800	650	80
8241072	Cyclone Slim 3 79W Warm	1100	950	80
8241073	Cyclone Slim 3 79W Neutral	1100	950	80
8241082	Cyclone Slim 4 99W Warm	1450	1300	80
8241083	Cyclone Slim 4 99W Neutral	1450	1300	80

For dimmer version add letter “D” at the end of product code.

* At dimmer version the driver is placed out of the body.

Colour Codes:

0

 Colours

1

 White

2

 Titan

3

 Black

CYCLONE

ARCHITECTURAL SURFACE & PENDANT LUMINAIRES



CYCLONE

ARCHITECTURAL SURFACE & PENDANT LUMINAIRES





CYCLONE

ARCHITECTURAL SURFACE & PENDANT LUMINAIRES



CYCLONE SLIM SMOOTH



Colour Codes:

0 Colours 1 White 2 Titan 3 Black



- Aluminium body, painted electrostatically in selected colour.
- High efficient satin cover.
- 4 pieces of suspension needed.
- CRI: min. 80 / SDCM: 3
- Luminous Efficacy:
203 Lm/W at 4000K 300mA
192 Lm/W at 3000K 300mA

UPON REQUEST

- In UP DOWN editions.

Code	Description	Dimensions mm			
		ØA	ØB	C	D
8301052	Cyclone Slim 1 Smooth 34W Warm*	600	450	80	125
8301053	Cyclone Slim 1 Smooth 34W Neutral*	600	450	80	125
8301062	Cyclone Slim 2 Smooth 45W Warm	800	650	80	200
8301063	Cyclone Slim 2 Smooth 45W Neutral	800	650	80	200
8301072	Cyclone Slim 3 Smooth 69W Warm	1100	950	80	320
8301073	Cyclone Slim 3 Smooth 69W Neutral	1100	950	80	320
8301082	Cyclone Slim 4 Smooth 89W Warm	1450	1300	80	450
8301083	Cyclone Slim 4 Smooth 89W Neutral	1450	1300	80	450

For dimmer version add letter “D” at the end of product code.

* At dimmer version the driver is placed out of the body.



CYCLONE

ARCHITECTURAL SURFACE & PENDANT LUMINAIRES





CYCLONE

CYCLONE TR



CYCLONE SLIM TR



Colour Codes:

0 Colours 1 White 2 Titan 3 Black

ARCHITECTURAL SURFACE & PENDANT LUMINAIRES



- Aluminium body, painted electrostatically in selected colour.
- High efficient satin cover.
- CRI: min. 80 / SDCM: 3
- Luminous Efficacy:
203 Lm/W at 4000K 300mA
192 Lm/W at 3000K 300mA
- Upon request in Up Down edition.

Code	Description	Dimensions mm				
		A	B	C	D(R)	E
8241172	Cyclone 1 TR 53W Warm	760	480	800	240	120
8241173	Cyclone 1 TR 53W Neutral	760	480	800	240	120
8241182	Cyclone 2 TR 75W Warm	1020	740	1100	240	120
8241183	Cyclone 2 TR 75W Neutral	1020	740	1100	240	120
8241192	Cyclone 3 TR 96W Warm	1320	1040	1450	240	120
8241193	Cyclone 3 TR 96W Neutral	1320	1040	1450	240	120

For dimmer version add letter “D” at the end of product code.





- Aluminium body, painted electrostatically in selected colour.
- High efficient satin cover.
- CRI: min. 80 / SDCM: 3
- Luminous Efficacy:
203 Lm/W at 4000K 300mA
192 Lm/W at 3000K 300mA
- Upon request in Up Down edition.

Code	Description	Dimensions mm				
		A	B	C	D(R)	E
8241202	Cyclone Slim 1 TR 50W Warm	700	550	750	175	80
8241203	Cyclone Slim 1 TR 50W Neutral	700	550	750	175	80
8241212	Cyclone Slim 2 TR 75W Warm	1000	850	1100	175	80
8241213	Cyclone Slim 2 TR 75W Neutral	1000	850	1100	175	80
8241222	Cyclone Slim 3 TR 96W Warm	1300	1150	1450	175	80
8241223	Cyclone Slim 3 TR 96W Neutral	1300	1150	1450	175	80



For dimmer version add letter “D” at the end of product code.

CYCLONE

CYCLONE SQ



CYCLONE SLIM SQ



Colour Codes:			
<u>0</u>	Colours	<u>1</u>	White
<u>2</u>	Titan	<u>3</u>	Black

ARCHITECTURAL SURFACE & PENDANT LUMINAIRES



- Aluminium body, painted electrostatically in selected colour.
- High efficient satin cover.
- CRI: min. 80 / SDCM: 3
- Luminous Efficacy:
203 Lm/W at 4000K 300mA
192 Lm/W at 3000K 300mA
- Upon request in Up Down edition.

Code	Description	Dimensions mm			
		A	B	C(R)	D
8241232	Cyclone 1 SQ 56W Warm	800	520	240	120
8241233	Cyclone 1 SQ 56W Neutral	800	520	240	120
8241242	Cyclone 2 SQ 85W Warm	1100	820	240	120
8241243	Cyclone 2 SQ 85W Neutral	1100	820	240	120
8241252	Cyclone 3 SQ 113W Warm	1450	1170	240	120
8241253	Cyclone 3 SQ 113W Neutral	1450	1170	240	120

For dimmer version add letter “D” at the end of product code.



- Aluminium body, painted electrostatically in selected colour.
- High efficient satin cover.
- CRI: min. 80 / SDCM: 3
- Luminous Efficacy:
203 Lm/W at 4000K 300mA
192 Lm/W at 3000K 300mA
- Upon request in Up Down edition.

Code	Description	Dimensions mm			
		A	B	C(R)	D
8241262	Cyclone Slim 1 SQ 70W Warm	850	700	175	80
8241263	Cyclone Slim 1 SQ 70W Neutral	850	700	175	80
8241272	Cyclone Slim 2 SQ 99W Warm	1150	1000	175	80
8241273	Cyclone Slim 2 SQ 99W Neutral	1150	1000	175	80
8241282	Cyclone Slim 3 SQ 126W Warm	1450	1300	175	80
8241283	Cyclone Slim 3 SQ 126W Neutral	1450	1300	175	80

For dimmer version add letter “D” at the end of product code.

CYCLONE






ARCHITECTURAL SURFACE & PENDANT LUMINAIRES





CYCLONE

CYCLONE PART



Colour Codes:

0 Colours 1 White 2 Titan 3 Black

ARCHITECTURAL SURFACE & PENDANT LUMINAIRES



- Aluminium body, painted electrostatically in selected colour.
- High efficient satin cover.
- CRI: min. 80 / SDCM: 3
- Luminous Efficacy:
203 Lm/W at 4000K 300mA
192 Lm/W at 3000K 300mA
- Upon request in Up Down edition.

Code	Description	Dimensions mm		
		ØA	B	C ^(e)
8241292	Cyclone 5 Part 46W Warm	2000 - 1720	1700	120
8241293	Cyclone 5 Part 46W Neutral	2000 - 1720	1700	120
8241302	Cyclone 6 Part 43W Warm	3000 - 2720	1600	72
8241303	Cyclone 6 Part 43W Neutral	3000 - 2720	1600	72
8241312	Cyclone 7 Part 43W Warm	4000 - 3720	1735	51
8241313	Cyclone 7 Part 43W Neutral	4000 - 3720	1735	51
8241322	Cyclone 8 Part 53W Warm	5000 - 4720	2050	51
8241323	Cyclone 8 Part 53W Neutral	5000 - 4720	2050	51

For dimmer version add letter “D” at the end of product code.



- Aluminium body, painted electrostatically in selected colour.
- High efficient satin cover.
- CRI: min. 80 / SDCM: 3
- Luminous Efficacy:
203 Lm/W at 4000K 300mA
192 Lm/W at 3000K 300mA
- Upon request in Up Down edition.

Code	Description	Dimensions mm		
		A	B	C
8241332	Cyclone 9 Part 29W Warm	1200	140	120
8241333	Cyclone 9 Part 29W Neutral	1200	140	120
8241342	Cyclone 10 Part 16W Warm	600	140	120
8241343	Cyclone 10 Part 16W Neutral	600	140	120
8241352	Cyclone 11 Part 8W Warm	300	140	120
8241353	Cyclone 11 Part 8W Neutral	300	140	120

For dimmer version add letter “D” at the end of product code.



CYCLONE

ARCHITECTURAL SURFACE & PENDANT LUMINAIRES



CYCLONE

CYCLONE SLIM SYSTEM



ARCHITECTURAL SURFACE & PENDANT LUMINAIRES



- Aluminium body, painted electrostatically in selected colour.
- High efficient satin cover.
- CRI: min. 80 / SDCM: 3
- Luminous Efficacy:
203 Lm/W at 4000K 300mA
192 Lm/W at 3000K 300mA






Code	Description	Dimensions mm		
		A	B	C
8241612	Cyclone Slim System L1200 29W Warm	1200	75	80
8241613	Cyclone Slim System L1200 29W Neutral	1200	75	80
8241622	Cyclone Slim System L1500 35W Warm	1500	75	80
8241623	Cyclone Slim System L1500 35W Neutral	1500	75	80
8241632	Cyclone Slim System L1800 42W Warm	1800	75	80
8241633	Cyclone Slim System L1800 42W Neutral	1800	75	80
8241642	Cyclone Slim System L2100 48W Warm	2100	75	80
8241643	Cyclone Slim System L2100 48W Neutral	2100	75	80
8241652	Cyclone Slim System L2700 62W Warm	2700	75	80
8241653	Cyclone Slim System L2700 62W Neutral	2700	75	80

For dimmer version add letter “D” at the end of product code.

Colour Codes:			
0	Colours	1	White
2	Titan	3	Black

CYCLONE

CYCLONE SLIM SYSTEM



ARCHITECTURAL SURFACE & PENDANT LUMINAIRES






- Aluminium body, painted electrostatically in selected colour.
- High efficient satin cover.
- CRI: min. 80 / SDCM: 3
- Luminous Efficacy:
203 Lm/W at 4000K 300mA
192 Lm/W at 3000K 300mA

Code	Description	Dimensions mm		
		ØA	B	C ^(a)
8241662	Cyclone Slim System D 800 -180° 25W Warm	800 - 650	800	180
8241663	Cyclone Slim System D 800 -180° 25W Neutral	800 - 650	800	180
8241672	Cyclone Slim System D1100 -180° 38W Warm	1100 - 950	1100	180
8241673	Cyclone Slim System D1100 -180° 38W Neutral	1100 - 950	1100	180
8241682	Cyclone Slim System D1450 - 90° 22W Warm	1450 - 1300	1025	90
8241683	Cyclone Slim System D1450 - 90° 22W Neutral	1450 - 1300	1025	90
8241692	Cyclone Slim System D1450 -180° 48W Warm	1450 - 1300	1450	180
8241693	Cyclone Slim System D1450 -180° 48W Neutral	1450 - 1300	1450	180
8241702	Cyclone Slim System D2000 - 45° 18W Warm	2000 - 1850	765	45
8241703	Cyclone Slim System D2000 - 45° 18W Neutral	2000 - 1850	765	45
8241712	Cyclone Slim System D2000 - 90° 35W Warm	2000 - 1850	1415	90
8241713	Cyclone Slim System D2000 - 90° 35W Neutral	2000 - 1850	1415	90
8241722	Cyclone Slim System D2000 -120° 48W Warm	2000 - 1850	1730	120
8241723	Cyclone Slim System D2000 -120° 48W Neutral	2000 - 1850	1730	120
8241732	Cyclone Slim System D2500 - 45° 22W Warm	2500 - 2350	955	45
8241733	Cyclone Slim System D2500 - 45° 22W Neutral	2500 - 2350	955	45
8241742	Cyclone Slim System D2500 - 90° 45W Warm	2500 - 2350	1770	90
8241743	Cyclone Slim System D2500 - 90° 45W Neutral	2500 - 2350	1770	90
8241752	Cyclone Slim System D3000 - 45° 28W Warm	3000 - 2850	1150	45
8241753	Cyclone Slim System D3000 - 45° 28W Neutral	3000 - 2850	1150	45
8241762	Cyclone Slim System D3000 - 72° 42W Warm	3000 - 2850	1765	72
8241763	Cyclone Slim System D3000 - 72° 42W Neutral	3000 - 2850	1765	72
8241772	Cyclone Slim System D3500 - 45° 32W Warm	3500 - 3350	1340	45
8241773	Cyclone Slim System D3500 - 45° 32W Neutral	3500 - 3350	1340	45
8241782	Cyclone Slim System D3500 - 60° 42W Warm	3500 - 3350	1750	60
8241783	Cyclone Slim System D3500 - 60° 42W Neutral	3500 - 3350	1750	60
8241792	Cyclone Slim System D4000 - 51° 42W Warm	4000 - 3850	1725	51
8241793	Cyclone Slim System D4000 - 51° 42W Neutral	4000 - 3850	1725	51
8241802	Cyclone Slim System D4500 - 51° 45W Warm	4500 - 4350	1940	51
8241803	Cyclone Slim System D4500 - 51° 45W Neutral	4500 - 4350	1940	51
8241812	Cyclone Slim System D5000 - 51° 52W Warm	5000 - 4850	2150	51
8241813	Cyclone Slim System D5000 - 51° 52W Neutral	5000 - 4850	2150	51

For dimmer version add letter "D" at the end of product code.

CYCLONE

CYCLONE SLIM SYSTEM








ARCHITECTURAL SURFACE & PENDANT LUMINAIRES



- Aluminium body, painted electrostatically in selected colour.
- High efficient satin cover.
- CRI: min. 80 / SDCM: 3
- Luminous Efficacy:
203 Lm/W at 4000K 300mA
192 Lm/W at 3000K 300mA

Code	Description	Dimensions mm		
		R	A	B ^(a)
8241822	Cyclone Slim System R250 - 90° 28W Warm	250	700	90
8241823	Cyclone Slim System R250 - 90° 28W Neutral	250	700	90
8241832	Cyclone Slim System R400 - 90° 32W Warm	400	800	90
8241833	Cyclone Slim System R400 - 90° 32W Neutral	400	800	90
8241842	Cyclone Slim System R200 - 45° 28W Warm	200	620	45
8241843	Cyclone Slim System R200 - 45° 28W Neutral	200	620	45
8241852	Cyclone Slim System R200 - 60° 28W Warm	200	640	60
8241853	Cyclone Slim System R200 - 60° 28W Neutral	200	640	60
8241862	Cyclone Slim System R200 -135° 32W Warm	200	700	135
8241863	Cyclone Slim System R200 -135° 32W Neutral	200	700	135

For dimmer version add letter “D” at the end of product code.




Colour Codes:

0 Colours 1 White 2 Titan 3 Black






CYCLONE

ARCHITECTURAL SURFACE & PENDANT LUMINAIRES



CYCLONE

CYCLONE SLIM SMOOTH PART



Colour Codes:

0 Colours 1 White 2 Titan 3 Black

ARCHITECTURAL SURFACE & PENDANT LUMINAIRES



- Aluminium body, painted electrostatically in selected colour.
- High efficient satin cover.
- CRI: min. 80 / SDCM: 3
- Luminous Efficacy:
203 Lm/W at 4000K 300mA
192 Lm/W at 3000K 300mA

UPON REQUEST

- In UP DOWN editions.

Code	Description	Dimensions mm		
		ØA	B	C ^(o)
8301362	Cyclone Slim 5 Part Smooth 50W Warm	2000 - 1850	1700	120
8301363	Cyclone Slim 5 Part Smooth 50W Neutral	2000 - 1850	1700	120
8301372	Cyclone Slim 6 Part Smooth 43W Warm	3000 - 2850	1675	72
8301373	Cyclone Slim 6 Part Smooth 43W Neutral	3000 - 2850	1675	72
8301382	Cyclone Slim 7 Part Smooth 43W Warm	4000 - 3850	1670	51
8301383	Cyclone Slim 7 Part Smooth 43W Neutral	4000 - 3850	1670	51
8301392	Cyclone Slim 8 Part Smooth 53W Warm	5000 - 4850	2100	51
8301393	Cyclone Slim 8 Part Smooth 53W Neutral	5000 - 4850	2100	51

For dimmer version add letter "D" at the end of product code.



- Aluminium body, painted electrostatically in selected colour.
- High efficient satin cover.
- CRI: min. 80 / SDCM: 3
- Luminous Efficacy:
203 Lm/W at 4000K 300mA
192 Lm/W at 3000K 300mA

UPON REQUEST

- In UP DOWN editions.

Code	Description	Dimensions mm		
		A	B	C
8301402	Cyclone Slim 9 Part Smooth 29W Warm	1200	75	80
8301403	Cyclone Slim 9 Part Smooth 29W Neutral	1200	75	80
8301412	Cyclone Slim 10 Part Smooth 16W Warm	600	75	80
8301413	Cyclone Slim 10 Part Smooth 16W Neutral	600	75	80
8301422	Cyclone Slim 11 Part Smooth 8W Warm	300	75	80
8301423	Cyclone Slim 11 Part Smooth 8W Neutral	300	75	80

For dimmer version add letter "D" at the end of product code.

CYCLONE

ARCHITECTURAL SURFACE & PENDANT LUMINAIRES



CYCLONE

ARCHITECTURAL SURFACE & PENDANT LUMINAIRES




CYCLONE

ARCHITECTURAL SURFACE & PENDANT LUMINAIRES



CYCLONE

SINGLE ADJUSTABLE SUSPENSION



POWER SUPPLY



POWER SUPPLY



Colour Codes:

0 Colours 1 White 2 Titan 3 Black

ARCHITECTURAL SURFACE & PENDANT LUMINAIRES



- Stainless steel cable and regulators.
- **Required:**
3 pieces for each CYCLONE/CYCLONE SLIM luminaire
4 pieces for CYCLONE SLIM SMOOTH luminaire

Code	Description	L	Kg
900111	Single Suspension	500	0,050
900112	Single Suspension	1000	0,100
900113	Single Suspension	1500	0,150
900114	Single Suspension	2000	0,200
900116	Single Suspension	3000	0,300



- Plastic body.
- With transparent cable 3x0,75mm² or 5x0,50mm² for dimmer.

Code	Description	L	Kg
900122	Power Supply 3x0,75mm ² with Rosette Ø75	1000	0,120
900124	Power Supply 3x0,75mm ² with Rosette Ø75	2000	0,240
900126	Power Supply 3x0,75mm ² with Rosette Ø75	3000	0,360
900127	Power Supply 3x0,75mm ² with Rosette Ø75	4000	0,500
900162	Power Supply 5x0,50mm ² with Rosette Ø75	1000	0,120
900164	Power Supply 5x0,50mm ² with Rosette Ø75	2000	0,240
900166	Power Supply 5x0,50mm ² with Rosette Ø75	3000	0,360
900167	Power Supply 5x0,50mm ² with Rosette Ø75	4000	0,500



- For pendant use.
- Body from aluminium profile.
- With transparent cable 3x0,75mm² or 5x0,50mm² for dimmer.
- Square or round version.

Code	Description	Kg
90042	Power Supply 3x0,75mm ² L 2m Ø80	0,130
90043	Power Supply 3x0,75mm ² L 2m Ø70	0,130
90044	Power Supply 3x0,75mm ² L 2m 80x80	0,210
90045	Power Supply 3x0,75mm ² L 2m 70x70	0,200
90048	Power Supply 5x0,50mm ² L 2m Ø100	0,250
90049	Power Supply 5x0,50mm ² L 2m 100x100	0,300

CYCLONE

ARCHITECTURAL SURFACE & PENDANT LUMINAIRES

