



*Surface wall mounted luminaire with halogen or led lamp.
It is ideal for a wide range of outdoor applications due to it's high
protection degree IP65.
Available with one or two-way light distribution.*

Technical Features

- Aluminium body, painted electrostatically in selected colour.
- Die-cast aluminium lampholder - mounting base.
- Tempered protection glass.
- Silicone sealant.




To ensure the degree of protection (sealing), the use of flexible power supply cable type H07RN-F (in appropriate diameter) is required.

BEAM 5/6 IP65

OUTDOOR


BEAM 5 - ONE WAY



- For PAR 16/GU10 lamp.
- Aluminium body.

Code	Description	Kg
85754	BEAM5 1x50W PAR16 (LED, FLUO) / GU10	0,530


BEAM 5 - TWO WAY



- For PAR 16/GU10 lamp.
- Aluminium body.

Code	Description	Kg
85755	BEAM5 2x50W PAR16 (LED, FLUO) / GU10	0,530


BEAM 6 - ONE WAY



- For PAR 16/GU10 lamp.
- Aluminium body.

Code	Description	Kg
85769	BEAM6 1x50W PAR16 (LED, FLUO) / GU10	0,920

BEAM 6 - TWO WAY



- For PAR 16/GU10 lamp.
- Aluminium body.

Code	Description	Kg
85768	BEAM6 2x50W PAR16 (LED, FLUO) / GU10	0,920

0

Colours

1

White

2

Titan

3

Black

4

Chrome



