



*A recessed compact spot with rotation. It can satisfy multiple lighting requirements and it a perfect choice for houses, galleries, museums and retail areas.*

*Last generation light sources, ensure excellent performance with maximum energy efficiency. This, in combination with an efficient thermal management, makes SOL 3 a warranty for premium lighting with LED technology.*

#### **Technical Features**

- Recessed with frame in round shape, painted electrostatically in selected colour from die-cast aluminium.
- Internal adjustable ring from die-cast aluminium.
- Easy mounting.
- Pure light without IR/UV radiation.
- Die cast aluminum heatsink anodized.
- Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10).
- Connection for operation with Constant Current.

#### **Upon request:**

Available with highest colour rendering index (CRI)

SOL 3

Recessed Spotlights & Downlights

CE

F

IP 20

LED

850°C


5 YEARS WARRANTY

ta 25°C

not Included


60°

350°



- Beam: Medium, Wide.
- 12W power consumption driven at 350mA.
- CRI: min. 80 / SDCM: 3
- Luminous Efficacy:  
12W: 4000 K: 160 Lm/Watt  
12W: 3000 K: 155 Lm/Watt

Code	Description	Kg
86908	SOL 3 12W	0,500



		DRIVERS		DRIVERS DIMMER
		350mA 15W	350mA 25W	350mA 18W
		146,5x43,7x30	124x79x22	146,5x44x30
				Dali/Push B.
CODES	MODULES	800022	800041	800038
86908	SOL 3 12W	1 luminaire	1 - 2 luminaires	1 luminaire

LED COLOUR CODES:

2

 Warm

3

 Neutral

BEAM CODES:

02

 medium

03

 wide

Colour Codes:

0

 Colours

1

 White

2

 Titan

3

 Black

4

 Chrome

5

 matt Alum.