

With it's geometrical shape and it's uniformly illuminated opal cover,

PLEXI LINE gives the impression of an almost immaterial luminaire integrated in the ceiling. It is available in three dimensions and, for more accent lighting.

Technical Features

- Steel body, painted electrostatically in white colour.
- Aluminium spot base, painted electrostatically in selected colour.
- Opal plexi glass cover (for PLEXI LINE 300, 400, 640 editions).
- Pure light without IR/UV radiation.
- Efficient thermal management.
- Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10).


Upon Request

- Connection for emergency lighting system, for one or three hours.

/ 542 / www.petridis-lighting.gr

PLEXI LINE

PLEXI LINE 300 LED



ARCHITECTURAL RECESSED LUMINAIRES




- High efficient opal plexiglass cover.
- Suspension brackets included.
- CRI: min. 80 / SDCM: 3.
- Luminous Efficacy: 126 Lm/W at 4000K 120 Lm/W at 3000K

Code	Description	Dimensions				Holes mm
		Α	В	C	D	
82290121	Plexi Line 300 LED 22W Warm	310	310	282	105	284x284
82290131	Plexi Line 300 LED 22W Neutral	310	310	282	105	284x284

For dimmer version add letter " \mathbf{D} " at the end of product code.

PLEXI LINE 400 LED






- High efficient opal plexiglass cover.
- Suspension brackets included.
- CRI: min. 80 / SDCM: 3.
- Luminous Efficacy: 203 Lm/W at 4000K at 300mA 192 Lm/W at 3000K at 300mA

Code	Description	Dimensions				Holes mm
		Α	В	С	D	
82290521	Plexi Line 400 LED 29W Warm	410	410	382	105	384x384
82290531	Plexi Line 400 LED 29W Neutral	410	410	382	105	384x384

For dimmer version add letter "D" at the end of product code.

PLEXI LINE 640 LED







- High efficient opal plexiglass cover.
- Suspension brackets included.
- CRI: min. 80 / SDCM: 3.
- Luminous Efficacy: 189 Lm/W at 4000K at 350mA 182 Lm/W at 3000K at 350mA

Code	Description	Dimensions				Holes mm
		Α	В	C	D	
82290921	Plexi Line 640 LED 33W Warm	610	610	582	105	584x584
82290931	Plexi Line 640 LED 33W Neutral	610	610	582	105	584x584

For dimmer version add letter " \mathbf{D} " at the end of product code.

www.petridis-lighting.gr / 543 /